

PGE APPROVED STREET LIGHTING EQUIPMENT FOR NEW INSTALLATIONS

OUTDOOR LIGHTING SERVICES – 2018

PGE makes no representations or warranties regarding street lighting equipment, whether included or not included on this list of approved street lighting equipment. Inclusion on this list is not an endorsement of the equipment nor does it mean that the listed equipment is appropriate for requirements applicable to all street lighting applications. If equipment is not included in this list, it does not reflect whether or not such equipment is appropriate for street light owners other than PGE.

NON-LED

LUMINAIRES: COBRAHEAD, HORIZONTAL ROADWAY, FLAT LENS, GRAY

Size	Lens Type	Eaton (Previously Cooper)
70 W HPS 6400 Lumens (2053) (CU 1141)	Flat M-C-2 120/240V (factory wired 240V)	OVH70SNV2DH4
100 W HPS 9500 Lumens (2039) (CU 305)		OVH10SNV2DH4
150 W HPS 16000 Lumens (2042) (CU 306)		OVH15SNV2DH4
200 W HPS 22000 Lumens (2064) (CU 307)	Flat M-C-3 240V	OVF20SC43DH4
250 W HPS 29000 Lumens (2067) (CU 308)		OVF25SR43DH4
400 W HPS 50000 Lumens (2069) (CU 309)		OVF40SW43DH4

LUMINAIRES: COBRAHEAD, HORIZONTAL ROADWAY, FLAT LENS, BLACK

Size	Lens Type	Eaton (Previously Cooper)
70 W HPS 6400 Lumens (90003579)	Flat M-C-2 240V	OVH70SNV2DH4BK
100 W HPS 9500 Lumens (90003580)		OVH10SNV2DH4BK
150 W HPS 16000 Lumens (90003581)		OVH15SNV2DH4BK
200 W HPS 22000 Lumens (90003582)	Flat M-C-3 240V	OVF20SC43DH4BK
250 W HPS 29000 Lumens (90003583)		OVF25SN43DH4BK
400 W HPS 50000 Lumens (90003584)		OVF40SW43DH4BK

LUMINAIRES: POST-TOP, EARLY AMERICAN, BLACK

Size	Lens Type	Acuity Brands (AE)	General Electric
100 W HPS 9500 Lumens (2056) (CU 282)	M-S-2	247 10S XN MT2 R2 AY EC NL	T10R10S7N2AMS2BL160

LUMINAIRE: POST-TOP, CAPITOL ACORN, HPS, BLACK

Size	Lens Type	Hadco
100 W HPS 9500 Lumens (39540) (CU 1219)	M-S-5	S8867E
150 W HPS 16000 Lumens (39542) (CU 1220)		S8867G
200 W HPS 22000 Lumens (39541) (CU 1221)		S8867H
250 W HPS 29000 Lumens (39543) (CU 1222)		S8867I

LAMPS: HPS

Lamp Size	General Electric	Philips Lighting	Sylvania	EYE Lighting	Howard Lighting
70 W HPS 6300 Lumens (4455)	LU70	C70S62/ALTO	LU70	LU70	LU70
100 W HPS 9500 Lumens (4456)	LU100	C100S54/ALTO	LU100	LU100	LU100
150 W HPS 16000 Lumens (4458)	LU150/55	C150S55/ALTO	LU150/55	LU150/55	LU150/55
200 W HPS 22000 Lumens (4459)	LU200	C200S66/ALTO	LU200	LU200/EN	LU200
250 W HPS 29000 Lumens (4460)	LU250	C250S50/ALTO	LU250	LU250	LU250
400 W HPS 50000 Lumens (4462)	LU400	C400S51/ALTO	LU400	LU400	LU400

PHOTO CONTROL: STANDARD TWIST LOCK, ELECTRONIC, 105 TO 300 VOLT

Type	Acuity Brands (DTL)	Southconn Technologies (RIPLEY)
Photoelectric Control (1986)	D124-1.5-1704	6390TF-PGE

LED

LUMINAIRE: LED FLOOD, DIRECTIONAL, BRONZE, 3000K, 7 PIN

Size	Manu Part Number
128W LED Flood 16268 Lumens (90010393) (CU 288)	UFLD-C40-7030-D-U-66-Y-BZ-4N7-10K-U77436
184W LED Flood 23157 Lumens (90010248) (CU 289)	UFLD-C70-7030-D-U-66-Y-BZ-4N7-10K-U77437
371W LED Flood 46737 Lumens (90010394) (CU 766)	UFLD-L-C175-7030-D-U-66-Y-BZ-4N7-10K-U77439

LUMINAIRE: CREE LEDway, SILVER/GRAY (TYPE II)

Size	Cree
35 W LED 3064 Lumens (90002707) (CU 1350)	STR-LWY-2M-HT-02-E-UL-SV-525-40K-R
47 W LED 3830 Lumens (90002708) (CU1351)	STR-LWY-2M-HT-02-E-UL-SV-700-40K-R-UTL
53 W LED 4550 Lumens (90002709) (CU 1352)	STR-LWY-2M-HT-03-E-UL-SV-525-40K-R-UTL
66 W LED 6079 Lumens (90002710) (CU 1353)	STR-LWY-2M-HT-04-E-UL-SV-525-40K-R-UTL
100 W LED 9000 Lumens (90002711) (CU 1354)	STR-LWY-2M-HT-06-E-UL-SV-525-40K-R-UTL

LUMINAIRE: CREE LEDway, BRONZE (TYPE II) (Note: Use for shoebox replacements)

Size	Cree
35 W LED 3064 Lumens (90003419) (CU 1355)	STR-LWY-2M-HT-02-E-UL-BZ-525-40K-R
47 W LED 3830 Lumens (90003420) (CU 1356)	STR-LWY-2M-HT-02-E-UL-BZ-700-40K-R-UTL
53 W LED 4550 Lumens (90003421) (CU 1357)	STR-LWY-2M-HT-03-E-UL-BZ-525-40K-R-UTL
66 W LED 6079 Lumens (90003707) (CU 1358)	STR-LWY-2M-HT-04-E-UL-BZ-525-40K-R-UTL
100 W LED 9000 Lumens (90003708) (CU1359)	STR-LWY-2M-HT-06-E-UL-BZ-525-40K-R-UTL

LUMINAIRE: CREE LEDway, BLACK (TYPE II)

Size	Cree
35 W LED 3064 Lumens (90003452) (CU 1360)	STR-LWY-2M-HT-02-E-UL-BK-525-40K-R
47 W LED 3830 Lumens (90003453) (CU 1361)	STR-LWY-2M-HT-02-E-UL-BK-700-40K-R-UTL
53 W LED 4550 Lumens (90003454) (CU 1362)	STR-LWY-2M-HT-03-E-UL-BK-525-40K-R-UTL
66 W LED 6079 Lumens (90003709) (CU 1363)	STR-LWY-2M-HT-04-E-UL-BK-525-40K-R-UTL
100 W LED 9000 Lumens (90003710) (CU 1364)	STR-LWY-2M-HT-06-E-UL-BK-525-40K-R-UTL

SHIELD: CREE LEDway

SU 90004019

LUMINAIRE: LEOTEK, COBRA LED, GRAY, 3000K, 7 PIN

Size	Leotek
29W LED 3470 Lumens (90010244) (CU 1365)	GCJ1-20H-MV-WW-2R-GY-450-PCR7-RWG-WL-FDC-PGE
45W LED 5020 Lumens (90010246) (CU 1366)	GCJ2-20H-MV-WW-2R-GY-700-PCR7-RWG-WL-FDC-PGE
88W LED 10230 Lumens (90010247) (CU 1368)	GCM2-40H-MV-WW-2R-GY-700-PCR7-RWG-WL-FDC-PGE
160W LED 18700 Lumens (90010121) (CU 1431)	GCL1-80G-MV-WW-3R-GY-610-PCR7RWGWLFDCPGE

LUMINAIRE: LEOTEK, COBRA LED, BLACK, 3000K, 7 PIN

Size	Leotek
29 W LED 3470 Lumens (90010404) (CU 1375)	GCJ1-20H-MV-WW-2R-BK-450-PCR7-RWG-WL-FDC-PGE
45 W LED 5020 Lumens (90010405) (CU 1376)	GCJ2-20H-MV-WW-2R-BK-700-PCR7-RWG-WL-FDC-PGE
88 W LED 10230 Lumens (90010406) (CU 1378)	GCM2-40H-MV-WW-2R-BK-700-PCR7-RWG-WL-FDC-PGE

SHIELDS: LEOTEK FIXTURES

House side Shield for GC Leotek, Black snap on (90010243); Part# HSSGCJ
 **NOTE: order 1 for the JR fixture (28W & 45W), 2 for Med fixture (88W) and 4 for large fixture (160W)

LUMINAIRE: HADCO WESTBROOKE LED, BLACK (NON-FLARED, TYPE III)

Size	Hadco
35 W LED 4012 Lumens (90006684) (CU 1432)	C7897N/ CFX14
52 W LED 5818 Lumens (90004296) (CU 1397)	C7897CC-A3NN48A3NNNNA
68 W LED 7378 Lumens (90004297) (CU 1398)	C7897A / CF14
87 W LED 9913 Lumens (90004298) (CU 1399)	C7897B / CF14
136 W LED 12687 Lumens (90003665) (CU 1400)	C7897F / CF17

LUMINAIRE: HADCO WESTBROOKE LED, BLACK (FLARED, TYPE III)

Size	Hadco
35 W LED 4012 Lumens (90006685) (CU 1433)	C7897Y-A3NN32A3NNNNA
52 W LED 5818 Lumens (90004299) (CU 1402)	C7897Z-A3NN48A3NNNNA
68 W LED 7378 Lumens (90004300) (CU 1403)	C7897AA-A3NN64A3NNNNA
87 W LED 9913 Lumens (90004301) (CU 1404)	C7897BB-A3NN80A3NNNNA
136 W LED (90003667) (CU 1405)	C7897G / CF18

LUMINAIRE: POST-TOP, AMERICAN REVOLUTION LED, BLACK (TYPE II)

Size	Acuity Brands - AE
45 W LED 3395 Lumens (90007446) (CU 1442)	247L 20LEDE70 MVOLT 4K R2 AY TL
72 W LED 4409 Lumens (90007447) (CU 1443)	247L 20LEDE10 MVOLT 4K R2 AY TL

**LUMINAIRE: HOLOPHANE ACRYLIC WASHINGTON POSTLITE II LED ACORN,
3000K, Type III, 7 PIN**

Size	Holophane
60 W LED (90003664) (CU 1407) 6915 Lumens	AWDE2-P30-30K-AS-M-BK-3-N-S-BK

**LUMINAIRE: ACORN HOLOPHANE UTILITY WASHINGTON FCO, (No globe)
120-277V, 3000K, BLACK, TYPE III, 7PIN TOP MOUNT PC**

Size	Holophane
66 W LED (90003455) (CU 1408) 5,472 Lumens	WFCL2P30ASBKL3N RFD273694

LUMINAIRE: ACORN KING YARMOUTH GLOBELESS,120-277V, 3000K, BLACK, TYPE III, 7 PIN, DALI

Size	KING
60 W LED 4213 Lumens (90010210) (CU 1145)	K137-P4NG-III-60(SSL)-7030-120v-K14-PR7-3K-TB-DALI-RAL9017
75 W LED 4897 Lumens (90010211) (CU 1146)	K137-P4NG-III-75(SSL)-7030-120v-K14-PR7-3K-TB-DALI-RAL9017

SHIELDS FOR KING ACORN: SHIELD, LUMINARIE, 3 INCH, 120 DEGREES, KING LIGHTING

Size	KING
SU 90010232	K137HSS120D3H

LUMINAIRE: CREE XSP LED (TYPE III), NOT AVAILABLE FOR SCHEDULE 95, OPTION "A"

Size	CREE
25 W LED XSPR 2529 Lumens (90004975) (CU 1392)	BXSPRA03FG-USN
42 W LED XSPR 3819 Lumens (90004976) (CU 1393)	BXSPRA03FC-USN
56 W LED XSP2 5963 Lumens (90004978) (CU 1395)	BXSPBHT3MEB40KULSVN (Q4)
91 W LED XSP2 8747 Lumens (90004979) (CU 1396)	BXSPHT3MEB40KULSVN (Q8)

SHIELDS FOR CREE XSP LED, NOT AVAILABLE FOR SCHEDULE 95, OPTION "A"

Size	CREE
SHIELD FOR XSPR (25W & 42W) (90005110)	XA-SPRBLS
SHIELD FOR XSP1 (48W) (90005111)	XS-SP1BLS
SHIELD FOR XSP2 (56W & 91W) (90005112)	XA-SP2BLS

PHOTO CONTROL: EXTENDED LIFE TWIST LOCK, ELECTRONIC, 105 TO 300 VOLT

Type	Ripley	DTL	Intermatic *
Photoelectric Control (90002719)	RD8645	DLL 1271.5 J50	EK4536SB

STREETLIGHT, LED, VOLTAGE STICKER, 120V, 208V, 240V, 277V

Type

Voltage Sticker (90009772)	
-------------------------------	--

POLES AND MAST ARMS

POLES: ALUMINUM, SPUN, NATURAL AL FINISH, ANCHOR BASE

Length & Type	Valmont	Hapco	P&K Poles (Flagpole Inc)	Union Metal
25 Foot, 4' mast arm (1948) (CU 274) (0.156)	220840705T4SBF /1MA043240	21-362PGE	RTA7L25AAS1432D	150-B116-Y1
25 Foot, 4' mast arm (1949) (CU 275) (0.156) For O/H service	220845705T4J/1 MA0432B	54423PGE	NONE	150-B116-Y2
30 Foot, 6' mast arm (1951) (CU276) (0.156)	270845805T4/ 1MA0632B	21-585PGE	RTA8L30AAS1632D	150-B116-Y3
35 Foot, 8' mast arm (32942) (CU 326) (0.188)	3208-45806T4/ 1MA0832B45	21-867PGE	RTA8M35AAS1832D	150-B116-Y4
25 Foot, Davit 4' mast arm (1950) (CU 278) (0.156)	250075104D4	41-103PGE	RTA7L25AAD1432D	928-B23-Y1
30 Foot, Davit 6' mast arm (1952) (CU 279) (0.156)	3000-85106D4	41-176PGE	RTA8L30AAD1632D	920-B179-Y1
30 Foot Double Davit 2-6' mast arms (39138)(CU 1258) (0.156)	3000-856206D4Z	42-158XPGE	NONE	920-B180-Y1
35 Foot, Davit 8' mast arm (1953) (CU 280) (0.188)	3500-86108D4	41-231PGE	RTA8M35AAD1832D	920-B179-Y2
40 Foot, Davit 8' mast arm (1954) (CU 335) (0.219)	4000-87108D4	41-339PGE	RTA8H40AAD1832D	920-B179-Y3

POLE: DECORATIVE BLACK ALUMINUM (USE WITH HADCO UTILITY WESTBROOKE FIXTURE)

Length	Hadco
18 Foot, Black, Smooth Anchor Base (11" B.C.) (CU 1436)	CP2871C (40034)
4 Foot Pole Extension w/Arm Bracket, Pole Cap, AND 18 Foot Smooth Westbrook Pole (CU 1437)	CA7897-HFP710-P5A (90002579)
4 Foot Pole Extension w/Double Mast Arm, Pole Cap, AND 18 Foot Smooth Westbrook Pole (CU 1438)	CA2871L-HFP720-P5A (90003564)

Description	Part Number
Shroud for black Westbrook pole (90010254)	443580121845-A

POLES: DECORATIVE CAST ALUMINUM (USE WITH ACORN LUMINAIRES), FLUTED, BLACK COLOR, ANCHOR BASE

Length & Type	Hadco	Amerlux Exterior LLC	Pacific Lighting	Continental	Hapco*	Holophane
14 Foot, Post-Top, Decorative, Anchor Base (1963) (CU 331)	P-2065-14-A	D1305-14/BLK-PGE-GBL	DBCS-5F-14	PGE-14	77920PGE	WDA 14 F5J 17 P07 LAB BK
16 Foot, Post-Top Decorative, Anchor Base (1946) (CU 328)	P-2065-16-A	D1305-16/BLK-PGE-GBL	DBCS-5F-16	PGE-16	77920L 24PGE	WDA 16 F5J 17 P07 LAB BK

MOUNTING ARMS

SU#	Description	Part#
90010241	Banner Arm 5" RD TWIN BANNER ARM, 5" POST MOUNT, 24" ARM USE ONLY WITH HADCO 14' AND 16' ALUM POLES	BA52A24B-A
90010242	BRACKET FLOWER POT SINGLE, 5" POST MOUNT, 12" ARM LENGTH, BLACK COLOR USE ONLY WITH HADCO 14' AND 16' ALUM POLES	FPB5112-A

POLES: COMPOSITE, 1-PIECE, SMOOTH FINISH, ANCHOR BASE

Length	Color	CMT	Shakespeare
25 Foot (90009869) (CU 1500)	Black	N/A	AK25-16S1BB01
30 Foot (90003574) (CU 1501)	Black	MA30-D-50-(S6)-3-HS-PC-BC	AK30-16S1BB01
35 Foot (90003575) (CU 1502)	Black	MA35-D-50-(S6)-3-HS-PC-BC	AK35-18S1BB01
35 Foot * (39029) (CU 1503)	Gray	MA2-35-D-100-S1-HS-PC-NP-1B	AK35-18S2BB01

*Used for replacement of Option A painted steel poles in City of Salem

POLES: COMPOSITE, 2-PIECE, SMOOTH FINISH, DIRECT-BURIED, STUB PIECE ONLY

Use with Pole	Shakespeare	CMT
18 Foot, Post-Top	BHS1801N9BJ9901 (39351)	14-STUB-UP (39365)
20 Foot, Post-Top	BHS2001N1BJ9901 (39353)	16-STUB-UP (39367)
30 Foot, Mast Arm	BHS3099N3BL9901 (39357)	25-STUB-UP (39371)

35 Foot, Mast Arm	BXS3599N2BL9901 (39361)	30-STUB-UP (39375)
-------------------	----------------------------	-----------------------

POLES: COMPOSITE, 2-PIECE, SMOOTH FINISH, DIRECT-BURIED, TOP PIECE ONLY

Length & Type	Mounting Height & Color	Shakespeare	CMT
18 Foot, Post-Top*	14 Feet, Black	BHT1801S1BJ9901 (39350) (CU 1117)	TDS18-C-100-S3-HS-T300-NP-1B-22 (39364) (CU 1118)
18 Foot, Post-Top*	14 Feet, Bronze	BHT1801S5BJ9901 (39534) (CU 1127)	TDS18-C-100-S2-HS-T300-NP-1B-22 (39601)
20 Foot, Post-Top*	16 Feet, Black	BHT2001S1BJ9901 (39352) (CU 1120)	TDS20-D-100-S3-HS-PC-NP-1B-22 (39366) (CU 1121)
20 Foot Post-Top	16 Feet, Bronze	BHT2001S5BJ9901 (39354) (CU 1123)	TDS20-D-100-S2-HS-PC-NP-1B-22 (39368) (CU 1124)
30 Foot, Direct Buried	25 Feet, Gray	BHT3099S2BL9901 (39356) (CU 1105)	MDS30-F-100-S1-HS-PC-NP-1B-22 (39370) (CU 1106)
30 Foot, Direct Buried	25 Feet, Bronze	BHT3099S5BL9901 (39358) (CU 1111)	MDS30-F-100-S2-HS-PC-NP-1B-22 (39372) (CU 1112)
30 Foot Direct Buried	25 Feet, Black	BHT3099S1BL9901 (90002641) (CU 1113)	MDS30-F-100-3-HS-PC-NP-MH (90002643)
35 Foot, Direct-Buried	30 Feet, Gray	BXT3599S2BL9901 (39360) (CU 1108)	MDS35-F-100-S1-HS-PC-NP-1B-22 (39374) (CU 1109)
35 Foot, Direct-Buried	30 Feet, Bronze	BXT3599S5BL9901 (39362) (CU 1114)	MDS35-F-100-S2-HS-PC-NP-1B-22 (39376) (CU 1115)
35 Foot Direct-Buried	30 Feet, Black	BXT3599S1BL9901 (90002642)	MDS35-F-100-3-HS-PC-NP-MH (90002644)

Note: Post-top poles are normally for T&C fixtures but can be used for Acorn styles also. Poles 25' mounting height and above are for mast arm fixtures. * Shroud available

POLE FOOTINGS: CONCRETE

Precast Concrete Base	Bolt Circle	Bolt Projection	Bolt Type	Base Dimensions	Utility Vault Company
For 16 Foot Pole 1944 Only (146)	8 inch	2-¼ inch	3/4" -10 NC Galv Steel	18" Square by 48" High	4-LB
For all decorative and post-top anchor base poles 14 to 25 feet. (39083)	11 inch	3-1/2 inch	1"- 8 NC Galv Steel	20" Round by 48" High	20R-LB-4-PGE
For 25 to 35 Foot Aluminum Anchor Base Poles (147)				14" Square by 60" High	5CL-LB-PGE
For 40 Foot Al Poles (39094)				18" Top, 24" Bottom 84" High	7-LB

MAST ARMS: STEEL ARMS FOR WOOD POLES

Length	Valmont	Utility Metals	SALCO	Maclean Power Systems	WICO
2 foot, cantilever, no brace (2016) (CU 861)	ACSA-125-020		WP-125-2-S	S-125-2G	

4 foot, cantilever, no brace (2017) (CU 315)	ACSC 125-040	U125S040	WP-125-4-S	S-125-4G	
6 foot, cantilever, no brace (2018) (CU 316)		P125S060	WP-125-6-S	S-125-6G	
8 foot, single brace (2019) (CU 317)		S1252080	WPSG-125-8-S-PGE	S-125-8SG-30R	
10 foot, double brace (2020) (CU 318)		D125S100	WPDG-125-10-S	S-125-10DG	
12 foot, double brace (2021) (CU 319)		D125S120	WPDG-125-12-S	S-125-12DG	
14 foot, double brace (2022) (CU 320)		D125S140	WPDG-125-14-S	S-125-14DG	
18" Double Floodlight Unit, 2" Pipe, 18" Rise (38078) (CU 1022)			WP2F-2-1.5-S		
14" Single Floodlight Bracket 2901 (CU 1057)					WI-15-TL

MAST ARMS: FOR COMPOSITE POLES

Length, Finish	Whatley	SALCO	Valmont	Shakespeare
8" Bronze Finish Tenon-Mount (39498) (CU 329)			1HT90H30B (PWD DARK BRONZE)	OPAR-3T-0.7- BZ
8" Black Finish Tenon-Mount (90009810) (CU 1496)				OPAR-3T-0.7- BK
8" Bronze Finish AL or Steel (2025) (CU 350)	SB8-2DDB		1HS23808B475	OPAR-0.7-PGE-BR
6 Foot AL Finish (2026) (CU 751)	MA-72		IMA0632B475 W/HARDWARE	OPAR-6
6 Foot Bronze Finish (2027) (CU 775)	MA-72DDB		IMA0632B475-BRZ	OPAR-6-BRONZE
6 Foot Black Finish (90003576) (CU 1231)	MA-72DBL		IMA0632B475-BLK	OPAR-6-BK
8 Foot AL Finish (39202) (CU 1131)	MA-96		IMA0832B475	OPAR-8
8 Foot Bronze Finish (39201) (CU 1132)	MA-96DDB		IMA0832B475-BRZ	OPAR-8-BRONZE
8 Foot Black Finish (90003577) (CU 1232)	MA-96DBI		IMA0832B475-BLK	OPAR-8-BK
14" Single Floodlight Arm, AL Finish (38076 Arm+ 38077 Adapter) (CU 1023)		SFA-2A (Arm) + FA-A (Adapter)		

MAST ARM: TWIN DECORATIVE ARM FOR HADCO 14' OR 16' FLUTED CAST ALUM POLES

Hadco	Amerlux Exterior LLC
--------------	-----------------------------

PTH2520P3A (39480)	2BR50-3/GBL-PGE (39480)
-----------------------	----------------------------

MISCELLANEOUS

HANDHOLE COVER: GRAY, PLASTIC, STEEL CORE, UNIVERSAL

Quantum Engineering
TL-S (90004595)

STREETLIGHT WIRE: UNDERGROUND OR IN POLE

Streetlight Wire	Description
#10 CU 3-Conductor (00036) (CU 635) (Contact PGE for suppliers)	#10 AWG, 600 Volt, 3-Conductor, Class B Stranding, Type TC, with Sunlight-Resistant 45-mil PVC Jacket. Suitable for direct burial installations. Insulation to be black, red, and green per NEMA WC-7 for NEC applications (TFN, THWN, THHN), with fillers or binding tape added to produce round outer jacket, rated 90°C dry and 75°C wet, 1,000 ft NR reels. Jacket to display sequential footage markings. 2 reel labels, one attached to the outside flange surface, one attached to the drum wrapping; each to detail total footage, inside or starting footage.

JUNCTION BOX: FOR UNDERGROUND CONDUCTORS & CONNECTIONS

Junction Box Description	Junction Box, Concrete Polymer Lid, Fiberglass Reinforced Polymer flared sides, 18" Deep, No Floor, With Skid Resistant Cover Attached by Two Captive stainless steel 3/8-inch Penta-head Bolts, Gray Color, per PGE T&D Material Specification L26107 Note: 12"x12"x12" is 12 inches deep with straight sides. Covers must be marked ELECTRIC or POWER.
---------------------------------	---

Manufacturer	13" x 24" x 18" (90003478)	17" x 30" x 18" (90003480)	12" x 12" x 12" (39031)
Newbasis	FCA132418T-00043	FCA173018T-90026	PCA1212-90005 (Box: PMB121212SN20 Lid: SMC1212B1A20)
Quazite (Hubbell)	A42132418A017	A42173018A017	N/A
Oldcastle /Carson Industries	13241617	17301620	HLW1212-12-PC
CDR (Electrimold)	N/A	N/A	PA-13-1212-12
Highline	CHA132418HE1	CHA173018HE1	PHA121212SE1
Armorcast	A6001946TAX18-PGE	A6001640TAX18-PGE	A6001423TA (Box: A6001423) (Cover: A6001422)